



T4x Remote Control

Introducing the T4x remote control, flagship of the award-winning wireless interface lineup from RTI. Precision engineered with a large high-resolution capacitive touchscreen, the essential hard buttons, and a completely customizable interface, the user will enjoy simple, intuitive control and superb ergonomics. Perfectly suited for the smart home or office, the T4x sets the standard in wireless control with advanced features including grip sensors, WiFi, dual RF, and more.

Key Features

- Flush-mount, 4.0" high-resolution capacitive LCD touchscreen (480x800).
- Thin, sleek design with superb ergonomics.
- Two-way control using 2.4GHz (Zigbee®) and RTI control components.
- Dual RF transmission capability uses 433MHz and 2.4GHz (utilizing Zigbee® technology).
- Integrated 802.11b/g/n wireless Ethernet enables viewing MJPEG video, wireless program updates, enhanced two-way control and more.
- Integrated grip sensors keep the remote awake while in use.*
- Accelerometer provides “instant-on” control.*
- Twenty assignable/programmable keypad buttons for commonly used functions.
- Cursor button allows simple scrolling list navigation.
- System includes a Lithium-Ion battery and docking station.
- Transmits IR and RF (or both - on a single button press).
- Extremely wide IR transmitting frequency range.
- Completely customizable and programmable.
- Non-volatile Flash memory stores your system configuration even when power is not present.

Specifications

Power	3.6 VDC, 1800 mAh Lithium-Ion Battery Pack
Power Management	Integrated accelerometer / Grip sensors
Infrared Control Range	30 feet (9.1 meters) @ 60 degrees
Infrared Frequency Transmission Range	15kHz - 460kHz
Radio Frequency Control Range	Up to 100 feet (30.5 meters) (with optional System Interfaces/Processors)
Radio Frequency Carrier	802.15.4 @ 2.4GHz (Zigbee® Wireless Networking)433MHz
Wireless Ethernet	802.11b/g/n @ 2.4Ghz
Touchscreen Display	High-brightness color TFT LCDWVGA (480x800 pixels) with 16.7M colorsIntegrated high-resolution capacitive touchscreen
Display Size	4" (101mm) diagonal
Backlights	Blue/White LED (Keypad)
Nominal Run Time on Full Charge	4-6 hours, continuous use (WiFi® & backlight setting dependent)(5 to 7 days on average use)
Standby Time on Full Charge	30 Days
Battery Charge Time	3-4 Hours
Total System Memory	128M Bytes Flash (non-volatile) memory
Device Capability	Total number of devices is limited only by memory
Macro Capability	Unlimited steps in a single macroTotal number of macros is limited only by memoryMacro capability on every button
Communication	USB 2.0 10 pin connection port or via charging dock
Operating Temperature	+32°F to +122°F (0°C to +50°C)
Operating Humidity	5% to 95% Non-condensing
Dimensions (L x W x D)	8.3" (211mm) x 2.3" (58mm) x 0.8" (20mm)
Enclosure	High-impact molded ABS plastic
Weight	7.5 oz. (213g) with battery pack
Warranty	Three Years (Parts & Labor) / 1 year on the battery

All specifications subject to change without notice

* Grip sensors and accelerometer cannot be used simultaneously.



Remote Technologies Incorporated
5775 12th Avenue East, Suite 180, Shakopee, MN 55379
PH: (952) 253-3100 • Website: www.rticorp.com

RTI User Interfaces

Remote Controls	In-Wall Touchpanels
Keypads	Tabletop Touchpanels
Audio Control Keypads	Mobile Apps



RTI Control Accessories

Control Processors	IR Modules
System Kits	Relay Modules
RS-232 Modules	Z-Wave Modules



RTI Audio/Video Distribution

HDMI Splitters & Switchers	HDBaseT Extenders
HDMI Matrix Switchers	Presentation Switchers
HDBaseT Matrix Switchers	Video over IP Transceivers



RTI
It's Under Control®